





ABOUT US



Switchgear Factory, Navi Mumbai



Switchgear Factory, Ahmednagar



Switchgear Factory, Vadodara

Larsen & Toubro is a technology-driven company that infuses engineering with imagination. The Company offers a wide range of advanced solutions in the field of Engineering, Construction, Electrical & Automation, Machinery and Information Technology.

L&T Switchgear, a part of the Electrical & Automation business, is India's largest manufacturer of low voltage switchgear, with the scale, sophistication and range to meet global benchmarks. With over seven decades of experience in this field, the Company today enjoys a leadership position in the Indian market with a growing international presence.

It offers a complete range of products including powergear, controlgear, industrial automation, building electricals & automation, power quality solutions, energy meters, and protective relays. These products conform to Indian and International Standards.

Products





Control Solution

MO Contactors- Complete Solution for OEMs

- Compact lesser panel space requirement
- DIN rail mounting facility for entire range enabling faster installation
- In-built surge suppressor for protection from voltage surges
- Common and click fit accessories like, add on block, mechanical interlock kit, for entire range - less inventory & faster installation
- Low VA consumption, lower control transformer size
- Direct mounting thermal overload relay
- Environment friendly RoHS compliant, future ready
- AC Coil voltages:- 24V, 42V, 48V, 110V, 220V, 240V, 360V, 380V 415V, 440V, 525V
- * standard coil voltages 24V, 110V, 220V, 240V, 415V, 440V AC

Compact

9-18A with 1NO+1NC



45mm

25-45A



45mm

50-70A



55mm

80-110A



70mm

Inbuilt surge suppressor to prevent voltage surges in control supply

Common & Click Fit Type Accessories



Mechanical Latch

Keeps contactor in closed condition even after removal of coil supply





- Ideal for logical operations
- Preferred in places of voltage fluctuation
- Saves energy as coil supply can be removed once contactor is picked up

Control Solution


Smart Links for easy and quick installation of motor feeder

MPCB DOL LINK CONTACTOR






Smart link for MPCB paralleling



MPCB (Motor Protection Circuit Breaker)

Compact motor feeder

- Range upto 63A
- Two ranges available -
 - Overload and short circuit protection
 - Only short circuit protection
- DIN rail mounting facility for entire range
- Comprehensive range of accessories like aux. contact block, trip alarm contacts, under-voltage release, shunt trip, external operating handle etc are available
- Padlock without external handle
- Positive isolations for operator safety



Control Solution



Optimum solution for your applications

MI, 3 Pole Contactor 6-150A

- DIN rail mounting facility upto 80A
- Coil on top design for 95A and above
- All accessories are available like aux add on block, surge suppressor and MIL kit
- Spares available for entire range
- Complementing MN thermal overload relay
- AC Coil voltages:- 110V, 220V, 240V, 415V,



Power contactor with DC coil

MDX, 3 Pole DC Contactor

- Range 9-110A
- DIN rail mounting facility for entire range
- In-built surge suppressor upto 38A
- Compact design
- Low VA consumption
- Ideal for DC control applications such as
 - Battery charging
 - UPS installations
 - Telecom
 - PLC equipped machineries
- DC coil voltages:- 24V, 48V, 110V and 220V



Compact solution for motor feeder

MX Mini Power Contactor

- Available in 6, 9 & 12A, AC-3 ratings
- Compact power contactor
- Available in AC and DC coil voltage
- In-built surge suppressor with DC contactor
- Direct mounting thermal overload relay
- AC coil voltages:- 24V, 110V, 120V, 220V, 240V, 380V 415V
- DC coil voltages:- 24V, 30, 48V, 110V, 125V, 220V

Compact & reliable control solution



MX Mini Control Contactor

- Compact control contactor
- Available in AC and DC coil voltage
- 4 pole control design
- Aux contacts extendable upto 8 with top add on block
- In-built surge suppressor with DC contactor
- Ideal for applications with complex control logic
- AC coil voltages:- 24V, 110V, 120V, 220V, 240V, 380V 415V
- DC coil voltages:- 24V, 30, 48V, 110V, 125V, 220V



Protection Solution



of accidental contact

MCB

For AC application

- Range 0.5A to 63A with breaking capacity of 10kA
- Range 80A, 100A & 125A at 15kA
- Tripping curves B, C & D in SP, DP, TP & FP
- Protection degree IP20
- Availability of wide range of accessories

For DC application

- Available in current ratings of 6A to 63A
- Rated voltage : 130V DC (for SP), 250V DC (for DP)
- Breaking capacity of 6kA, 10kA
- Protection degree IP20
- · Availability of wide range of accessories





Surge Protection Device (SPD)

- Available in Type 2 and Type 1+2
- Type 2: Protection against indirect lightning and switching surges
 - Maximum discharge current Imax 40kA and 15kA
 - Protection level Up 1.1kV
- Type 1+2 : Protection against direct and indirect lightning surges
 - Nominal discharge current In 20kA
 - Maximum discharge current Imax 50kA
 - Protection level Up 1.7kV

Protection Solution



Isolator

- Suitable for AC22-A utilization category
- Available in DP, TP and FP versions in 40A, 63A, 80A and 100A ratings
- Protection degree- IP20
- CE and KEMA certified



RCD


Available in Type AC & Type Adi

- RCCB Available in 25A to 100A ratings with 30mA,100mA & 300mA sensitivity in DP and FP
- RCBO

Wide range of current ratings - 6A to 63A with 10mA to 300mA sensitivity in DP and FP

*Adi (Added immunity)-For installations with presence of pulsating DC along with transients and harmonics

Moulded Case Circuit Breaker (MCCB)



- Range: 16A to 1250A
- No. of poles: 1P, 2P, 3P and 4P
- Breaking capacities:
 10kA/18kA/25kA/36kA/50kA/70kA/100kA
- Microprocessor and thermal magnetic protection
- MCCBs for motor back up protection
- MCCBs for distribution and SD versions
- Suitable for DC application
- Manual, rotary or motorized versions
- Wide range of common internal and external accessories




Panel Accessories



- 1 Ph & 3 Ph voltmeter, 1 Ph & 3 Ph ammeter, frequency meter, VAF+PF meter
- · Wide operating range of auxiliary supply
- Field programmable CT/PT ratio with password protection
- Auto scaling of kilo and mega
- Displays average and phase quantities*
- Auto and manual scrolling *
- Phase indication of displayed parameter through LED*
- Ammeter with secondary currents of 1A and 5A.
- * Applicable to 3 phase meters.









Timing Devices & Supply Monitors

- Accurate switching and reliable operation
- Solution for wide variety of applications
 - ON delay timer
 - True OFF delay timer
 - Star delta timer
 - Multifunction timer
 - One shot timer
 - Asymmetrical ON/OFF & OFF/ON timer

Supply Monitors

- Reliable detection of phase parameters such as phase loss, phase sequence, phase unbalance, neutral loss protection and wide range of selectable under voltage and over voltages protection
- Earth leakage relay monitors, detects and protects power systems from earth leakage faults with wide selectable range of 30mA to 30A

Panel Accessories



16 mm compact LED also available, Ideal for OEM panel

LED Indicators and Push Buttons

- Actuators and contact blocks with compact design and snap fit arrangement
- Actuators as ready to use solution for OEMs that provides IP65 protection with in-built NO+NC contacts
- Illuminated Push Button actuators with snap fit design for ease of assembly and low power consumption
- LED indicators with 1 lakh burning hours, with surge & low voltage glow protection
- Push Button Stations- robust, easy to grip & assemble
- 8 way Push Button pendant available with hanging provision in single speed mode for crane applications

Switches upto 12 ways & 12 poles available for various SPM applications



Rotary Switches & Cable Ducts

- Isolator switches (ON-OFF switches), Changeover switches (Local Remote, Auto Manual Switches), multistep switches available from a range of 6A-200A
- Ammeter selector switches & voltmeter selector switches
- Load break switches with padlock in AC23 utilization category
- Zero halogen & fire retardant low smoke cable ducts with snap fit and non-slip design.

Industrial Automation Solution

Built-in



AC Drive

- Range: 0.75kW to 90kW
- V/F, sensorless vector control, slip compensation
- Input voltage range 380 VAC to 480 VAC (-15% to + 10%)
- Built-in brake control
- Built-in PLC functionality
- Built-in PID
- Conformal coating complying to IEC 60721-3-3 class 3C2
- Built-in communication RS485 modbus RTU
- Built-in braking chopper till 30kW
- Ambient temperature 50°C
- Approvals: CE, UL RoHS

Detachable



Soft Starter

- Range: 23A to 1600A
- Built-in bypass contactor
- XLR-8 adaptive acceleration & deceleration control for pumps
- Large LCD keypad
- Power through operation allows to run soft starter even with one SCR shorted
- Conformal coated PCB
- Electronic motor overload protection
- 99 event logs with time stamping, last 8 trip logs
- Ambient temperature 50°C
- Communication options available
- Comprehensive motor protection
- Fully programmable overload trip
- Built-in RTD & thermistor inputs
- Auto detection of inline or inside delta power connection approval: CE

Industrial Automation Solution





PLC

- Expandable I/O module like remote I/O
- Support 4 x comm. port:
- EtherNet , USB, 2 x RS232/485
- Built-In etherNet 10/100 Mbps
- Built-In USB port
- Built-in 2 channels high speed serial port
- Web monitoring
- Supports various communication protocols
 - Ethernet based protocols: EtherNet/IP, Modbus/TCP, HTTP (web) server
 - Serial protocol: Modbus/RTU, ASCII
- Large memory:
 - 987KByte program memory
 - 128KByte data memory
- Supports 4G SD memory card
 - Backup to SD card (data log, program), recipe
- Built-in PID, HSC, PTO
- · Data log, recipe
- 3 Step powerful password
 - LXGPC Programming software
 - * Online editing
 - * Support multi-languages
 - * Support win XP/vista/7(32/64bit)



HMI

- Available from 4" to 15"
- High performance processor
 - 32bit RISC (ARM) processor
 - High speed(400MHz), reliable
- Mass memory
 - 26MB screen memory, 256KB back up memory
- High-definition TFT color LCD
 - 65,536 color, 4.3" wide, 480x272
- Various built-in interface
 - USB host/device, serial, ethernet, CF card, SD card

Download all L&T's digital technical documents with

DocWhiz v1.1

Product catalogues • User manuals • Application notes
• Drawings • Technical notes • Installation videos
Save time: Instant access to the latest updates
Save space: No need to print and maintain hard copies

www.Lntebg.com/docwhiz



Optimise Reactive Power Solutions with etaPRO v2.0

Save time: Instantly select the right capacitor-reactor and switchgear combo

Save money: Calculate monthly payback

Save effort: Directly export bills of materials to MS Excel **Discover more:** Learn improved techniques on RPM

www.Lntebg.com/etapro



Select the switchgear your customer needs with **Product/Whiz**

Save time: Type 2 co-ordination enables swift selection Save effort: Share the selection via SMS or e-mail Enhance productivity: Swift delivery reduces response time

Download from Google Play



Selection of AC drives on your finger tips through DriveWhiz

Save time: Instantly find the right solution for your Application **Save effort:** Send product enquiry using application **Enhance productivity:** Right Selection will help to reduce breakdowns

Download from Google Play



Get the Switchgear Training Edge!

Aimed at maximizing productivity, conserving energy, minimizing costs and enhancing safety, our Electrical & Automation training programmes have benefitted over 1.35 Lakh professionals in the last 28 years. These training programmes are highly beneficial as they provide right exposure and impart knowledge on selection, installation, maintenance and testing of Electrical & Automation Products.

So gain the advantage and go the extra mile with:

- 22 courses on contemporary topics
- Courses applicable to all switchgear brands
- Training Centers in Pune, Lucknow, Coonoor, Vadodara, Delhi & Kolkata
- · Blend of theory and practical experience

The typical training programmes cover:

- Low Voltage & Medium Voltage Switchgear
- Switchboard Electrical Design
- AC Drives & Building Management Solutions
- Protective Relays & Earthing
- Power Quality Solutions

Please contact any of the training centres for participation and detailed training programme schedule.



Pune

Larsen & Toubro Limited Switchgear Training Centre, T-156/157, MIDC Bhosari,

Pune - 411 026 Tel: 020 2712 0037 / 2712 0653

Fax: 020 2712 2933 E-mail: stc-pune@Lntebg.com



Lucknow

Larsen & Toubro Limited Switchgear Training Centre, C - 6 & 7, UPSIDC P. O. Sarojininagar, Lucknow - 226 008 Tol: 0522 247 6015 / 07044 544

Tel: 0522 247 6015 / 97944 54455

Fax: 0522 247 6015

E-mail: stc-lucknow@Lntebg.com



Coonoor

Larsen & Toubro Limited Switchgear Training Centre, Ooty-Coonoor Main Road Yellanahalli P.O., The Nilairin 643 243

The Nilgiris - 643 243 Tel.: 0423 251 7107 Fax: 0423 251 7158

E-mail: stc-coonoor@Lntebg.com



Vadodara

Larsen & Toubro Limited Switchgear Training Centre Behind L&T Knowledge City, Near Village Ankhol, Vadodara - 390019

Tel: 0265 2457805

E-mail: stc-vadodara@Lntebg.com



Delhi

Larsen & Toubro Ltd Switchgear Training Centre 32, Shivaji Marg, Near Motinagar Metro Station, New Delhi - 110015 Tel: 011 41419515 / 41419695 / 41419500 Fax: 011 41419600

E-mail: stc-delhi@Lntebg.com



Kolkata

Larsen & Toubro Limited Switchgear Training Centre 4th Floor, 3B, Shakespeare Sarani, Kolkata - 700071 Tel: 033 42005975 / 42005978

E-mail: stc-kolkata@Lntebg.com

Electrical Standard Products (ESP) Offices:

HEAD OFFICE

L&T Business Park, Tower 'B' / 3rd Floor Saki Vihar Road, Powai Mumbai 400 072

Tel: 022-67053229 Fax: 022-67051112 e-mail: cic@LNTEBG.com

BRANCH OFFICES

501, Sakar Complex I Opp. Gandhigram Rly. Station Ashram Road

Ahmedabad 380 009 Tel: 079-66304006-11 Fax: 079-66304005 e-mail: esp-ahm@LNTEBG.com

38, Cubbon Road, P. O. Box 5098 **Bengaluru 560 001** Tel: 080-25020100 / 25020324 Fax: 080-25580525 e-mail: esp-blr@LNTEBG.com

131/1, Zone II

Maharana Pratap Nagar **Bhopal 462 011** Tel: 0755-3080511 / 05 / 08 / 13 / 17 / 19

Fax: 0755-3080502

e-mail: esp-bho@LNTEBG.com

Plot No. 559, Annapurna Complex Lewis Road

Bhubaneswar 751 014

Tel: 0674-6451342 / 2436690 / 2436696

Fax: 0674-2537309

e-mail: esp-bsr@LNTEBG.com

Aspire Towers, 4th Floor Plot No. 55, Phase-I Industrial & Business Park Chandigarh-160 002

Tel: 0172-4646840 / 41 / 42 / 46 / 53 Fax: 0172-4646802

Email: esp-chd@Lntebg.com

L&T Construction Campus TC-1 Building, II Floor Mount-Poonamallee Road Manapakkam

Chennai 600 089 Tel: 044-2270 6800 Fax: 044-22706940

e-mail: esp-maa1@LNTEBG.com

67, Appuswamy Road Post Bag 7156 Opp. Nirmala College **Coimbatore 641 045** Tel: 0422-2588120 / 1 / 5 Fax: 0422-2588148

e-mail: esp-cbe@LNTEBG.com

Khairasol, Degaul Avenue **Durgapur 713 212**

Tel: 0343-2540448 / 2540449 / 2540443

Fax: 0343-2540442

e-mail: esp-dgp@LNTEBG.com

5, Milanpur Road, Bamuni Maidan **Guwahati 781 021**

Tel: +91 8876554410 / 8876554417

Fax: 361-2551308

e-mail: esp-ghy@LNTEBG.com

II Floor, Vasantha Chambers 5-10-173, Fateh Maidan Road

Hyderabad 500 004 Tel: 040-67015052 Fax: 040-23296468

e-mail: esp-hyd@LNTEBG.com

Monarch Building, 1st Floor D-236 & 237, Amrapali Marg Vaishali Nagar

Jaipur 302 021 Tel: 0141-4385914 to 18

Fax: 0141-4385925 e-mail: esp-jai@LNTEBG.com

Akashdeep Plaza, 2nd Floor

P. O. Golmuri

Jamshedpur 831 003

Jharkhand

Tel: 0657-2312205 / 38 Fax: 0657-2341250

e-mail: esp-jam@LNTEBG.com

Skybright Bldg; M. G. Road Ravipuram Junction, Ernakulam Kochi 682 016

Tel: 0484-4409420 / 4 / 5 / 7 Fax: 0484-4409426 e-mail: esp-cok@LNTEBG.com

3-B, Shakespeare Sarani Kolkata 700 071

Tel: 033-42005982 Fax: 033-22821025 / 7587 e-mail: esp-ccu@LNTEBG.com

A28, Indira Nagar, Faizabad Road Lucknow 226 016

Tel: 0522-4929905 / 04 Fax: 0522-2311671

e-mail: esp-Lko@LNTEBG.com

No: 73, Karpaga Nagar, 8th Street K. Pudur

Madurai 625 007

Tel: 0452-2567405 / 2561068 / 2561657

Fax: 0452-2567552

e-mail: esp-mdu@LNTEBG.com

L&T Business Park, Tower 'B' / 5th Floor Saki Vihar Road, Powai Mumbai 400 072

Tel: 022-67052874 / 2737 / 1156 Fax: 022-67051112 e-mail: esp-bom@LNTEBG.com

12, Shivaji Nagar North Ambajhari Road

Nagpur 440 010 Tel: 0712-2260012 / 6606421 Fax: 2260030 / 6606434 e-mail: esp-nag@LNTEBG.com

32, Shivaji Marg P. O. Box 6223 New Delhi 110 015 Tel: 011-41419514 / 5 / 6 Fax: 011-41419600 e-mail: esp-del@LNTEBG.com

L&T House P. O. Box 119

191/1, Dhole Patil Road **Pune 411 001**

Tel: 020-66033395 / 66033279 Fax: 020-26164048 / 26164910 e-mail: esp-pnq@LNTEBG.com

Crystal Tower, 4th Floor, G. E. Road Telibandha Raipur - 492 006

Tel: 0771-4283214

e-mail: esp-raipur@LNTEBG.com

3rd Floor Vishwakarma Chambers Majura Gate, Ring Road

Surat 395 002
Tel: 0261-2473726 Fax: 0261-2477078

e-mail: esp-sur@LNTEBG.com

Radhadaya Complex Old Padra Road Near Charotar Society Vadodara 390 007 Tel: 0265-6613610 / 1 / 2 Fax: 0265-2336184

e-mail: esp-bar@LNTEBG.com

Door No. 49-38-14/3/2, 1st floor, NGGO's Colony, Akkayyapalem, Visakhapatnam - 530 016 Tel: 0891-2791126 / 2711125

Fax: 0891-2791100

Email: esp-viz@LNTEBG.com

Product improvement is a continuous process. For the latest information and special applications, please contact any of our offices listed here. Product photographs shown are for representative purpose only.





Larsen & Toubro Limited, Electrical Standard Products

Powai Campus, Mumbai 400 072

Customer Interaction Center (CIC)

BSNL / MTNL (toll free): 1800 233 5858 Reliance (toll free): 1800 200 5858

Tel: 022 6774 5858, Fax: 022 6774 5859

E-mail: cic@Lntebg.com / Website www.Lntebg.com

Registered Office: L&T House, N. M. Marg, Ballard Estate, Mumbai 400 001, INDIA CIN: L99999MH1946PLC004768

SP 50868 050816